

CARLISLE SURE-SEAL® DRIP EDGE**GENERAL:**

Sure-Seal Drip Edge is available in two designs, Drip Edge I for covering one wood nailer and, Drip Edge II for covering two wood nailers. The Sure-Seal Drip Edge is supported by the Carlisle roofing system warranties and is FM I-90 approved.

TYPICAL PROPERTIES AND CHARACTERISTICS:

Fascia Dimensions:	Drip Edge I - 2½" (63 mm) Drip Edge II - 4" (100 mm)
Color/Metal Options:	5 colors in 24 gauge (0.6 mm) Kynar Coated Steel 17 colors in .032 (.8 mm) Aluminum Coil Kynar Mill Finish .032 Aluminum
Features:	90° angle anchor cleat for ease of installation over roof edge. Anchor cleat is pre-punched 12" (300 mm) o.c. and fascia is pre-punched 6" (150 mm). 1½" (38 mm) ring shank nails provided for improved holding power and pullout resistance for the anchor cleat and top flange. Concealed joint covers

CAUTIONS AND WARNINGS:

1. Material must be kept clean and dry during storage. A protective poly film is laminated to the Kynar fascia and must be removed during installation.
2. Use care to avoid puncturing the membrane during installation.

INSTALLATION:

See appropriate installation guide.

Carlisle, SecurEdge and Sure-Seal are trademarks of Carlisle Corporation.
Kynar is a registered trademark of Pennwalt Corporation.

©1999 Carlisle Corporation

7/99