

Target Sumps[™]

Target Sumps ship ready to install, require no field cuts and save valuable time on the roof. Multiple thicknesses and slopes are available to accommodate specific job conditions with no waste, thus reducing disposal fees.



SIZES AVAILABLE FOR OPTIMUM DRAINAGE

- » Multiple thicknesses and slopes to accommodate specific job conditions
- » Additional drain heights achieved by adding base layer material
- » 8' x 8' Hinged Target Sumps are available with Carlisle's Tapered InsulBase[®] and Tapered SecurShield[®] performance facers in 25 psi
- » 4' x 4' Target Sumps are available with Carlisle's SecurShield[®] facer in 25 psi

Standard Hinged Target Sumps (8' x 8' Panel Size) Minimum Slope Panel Maximum **Pieces Per** Thickness Thickness Package 0.5" 1.5" Х 14 1⁄4" G 1.0" 2.0" 10 Q 0.5" 2.5" 8 1⁄2" ΧХ 1.0" 3.0" 6 3⁄8" SS 0.5" 2.0" 10

REDUCES FIELD LABOR

- » 8' x 8' Hinged Target Sump ships 4' x 8', folds out to 8' x 8'
- » 4' x 4' Target Sump ships 4' x 4'
- » Pre-cut, ready to install
- » Factory assembled
- » Concentric circles simplify drain cutout

HELPS ELIMINATE WASTE

- » Reduces dumpster fees
- » Reduces impact on local landfills

Target Sumps (4' x 4' Panel Size) Slope Panel Minimum Maximum **Pieces Per** Thickness Thickness Package Q1 0.5" 1.5" 30 Q2 1.5" 2.5" 18 1⁄2" XX1 1.0" 2.0" 22 XX2 2.0" 3.0" 15